

CDN[®]

Measurement Tools



2024

CDNmeasurement.com



TABLE OF CONTENTS

Thermometers	3
Timers	17
Scales	20
Merchandising & Displays	26
Accessories	27

THERMOMETERS

Our high-precision thermometers offer unrivaled quality for those who demand the best. We take extra steps to ensure the quality, durability and accuracy of our thermometers. We also develop custom thermometers at our customers' requests. If you do not see your ideal thermometer in our collection, please ask us about developing a new one for you.

DIGITAL THERMOMETERS



DT392 – Digital Thermometer

-50 to +392°F/-45 to +200°C

- One-button operation
- Temperature guide
- 3 mm tip; 5"/12.7 cm stem

DT392

0 18436 00609 1



DT572 – Digital Folding Thermometer

-58 to +572°F/-50 to +300°C

- 4-second response
- Waterproof (IPX6)
- 1.7 mm thin tip; 3.375" (8.6 cm) stem

■ Black DT572-BK 0 18436 00509 4

■ Red DT572-R 0 18436 00515 5

■ Green DT572-G 0 18436 00516 2

■ Blue DT572-B 0 18436 00517 9



DT450X – Digital Pocket Thermometer

-40 to +450°F/-40 to +230°C

- 6-second response
- Hold
- 2.5 mm reduced tip; 2.75" (7.0 cm) stem

■ Black DT450X 0 18436 00457 8

■ Red DT450X-R 0 18436 00471 4

■ Green DT450X-G 0 18436 00473 8

■ Blue DT450X-B 0 18436 00474 5



DTT450 – Thin Tip Pocket Thermometer

-40 to +450°F/-40 to +230°C

- 4-second response
- One-button field calibration
- Hold
- 1.5 mm thin tip; 2.75" (7.0 cm) stem

■ Yellow DTT450 0 18436 00461 5

■ Red DTT450-R 0 18436 00477 6

■ Green DTT450-G 0 18436 00478 3

■ Blue DTT450-B 0 18436 00479 0



DTQ450X – Thin Tip Thermometer

-40 to +450°F/-40 to +230°C

- 6-second response
- Waterproof (IPX6)
- One-button field calibration
- 1.5 mm thin tip; 4.75" (12.1 cm) stem

0 18436 00458 5





Q2-450X – Heavy Duty Thin Tip Thermometer

-40 to +450°F/-40 to +230°C

- 6-second response
- Waterproof (IPX6)
- One-button field calibration
- 1.5 mm thin tip; 2.75" (7.0 cm) stem

0 18436 00459 2



DTTW572 – Waterproof Thin Tip Thermometer

-40 to +572°F/-40 to +300°C

- 4-second response
- Waterproof (IPX7)
- One-button field calibration
- 180° rotating display
- 1.5 mm thin tip; 3.5" (8.9 cm) stem

0 18436 00507 0



DTL572 – Lollipop Thermometer

-40 to +572°F/-40 to +300°C

- 4-second response
- One-button field calibration
- Hold
- 1.5 mm thin tip; 4.3" (11.0 cm) stem

Yellow	DTL572-Y	0 18436 00511 7
Red	DTL572-R	0 18436 00512 4
Green	DTL572-G	0 18436 00513 1
Blue	DTL572-B	0 18436 00514 8



DTW450 – Dishwasher Thin Tip Thermometer

-40 to +450°F/-40 to +230°C

- 6-second response
- Safe for commercial dishwashers (IPX7)
- One-button field calibration
- 1.5 mm thin tip; 4.5" (11.4 cm) stem

0 18436 00462 2



DTW450L – Waterproof Thermometer – Long Stem

-40 to +450°F/-40 to +230°C

- 6-second response
- Safe for commercial dishwashers (IPX7)
- One-button field calibration
- 2.5 mm reduced tip; 8" (20.3 cm) stem

0 18436 00469 1



COOKING THERMOMETERS



IR220 – Cooking Thermometer

60 to 220°F

- Safe for commercial dishwashers
- Field calibration
- 1" (2.5 cm) magnified dial; 5" (12.7 cm) stem

0 18436 00200 0



IRL220 – Large Dial Cooking Thermometer

60 to 220°F

- Safe for commercial dishwashers
- Boil test field calibration
- 1.75" (4.4 cm) dial; 5" (12.7 cm) stem

0 18436 00201 7



IRT220 – Cooking Thermometer

0 to 220°F

- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1" (2.5 cm) magnified dial; 5" (12.7 cm) stem
- Private label options available



IRT220

0 18436 00202 4

IRT220-X2 Twin Pack

0 18436 00218 5

IRT220C Celsius

0 18436 00740 1



IRT220-PACK – Cooking Thermometer Display Pack

0 to 220°F

- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1" (2.5 cm) magnified dial; 5" (12.7 cm) stem
- 12 per pack



IRT220-PACK

0 18436 00205 5

IRT220C-PACK Celsius

0 18436 00211 6




IRT550 – High Temperature Cooking Thermometer

50 to 550°F

- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1" (2.5 cm) magnified dial; 5" (12.7 cm) stem

0 18436 00209 3



IRXL220 – Large Dial Cooking Thermometer

0 to 220°F

- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1.75" (4.4 cm) dial; 5" (12.7 cm) stem



IRXL220

0 18436 00212 3

IRXL220C Celsius

0 18436 00716 6



MYT200 – Meat/Yeast Thermometer

100 to 200°F/38 to 93°C

- Temperature guide
- Ovenproof
- Dishwasher safe
- Non-mercuric glass column in stainless steel

0 18436 00505 6



IRM190 – Ovenproof Meat Thermometer

130 to 190°F/50 to 90°C

- Temperature guide
- Boil test field calibration
- 1.75" (4.4 cm) dial; 5" (12.7 cm) stem

IRM190

0 18436 00203 1

IRM190C

Celsius

0 18436 00745 6



IRM200 – Ovenproof Meat Thermometer

120 to 200°F/50 to 100°C

- Temperature guide
- Safe for commercial dishwashers
- Boil test field calibration
- Extra-large 2" (5.1 cm) dial; 5" (12.7 cm) stem

0 18436 00207 9



IRM200-GLOW – Ovenproof Meat Thermometer – Glow

120 to 200°F/50 to 100°C

- Easy to read in low light conditions
- Temperature guide
- Safe for commercial dishwashers
- Boil test field calibration
- Extra-large 2" (5.1 cm) dial; 5" (12.7 cm) stem

0 18436 00213 0



IRL500 – Long Stem Fry Thermometer – 12"

100 to 500°F/38 to 260°C

- Safe for commercial dishwashers
- Boil test field calibration
- 1.75" (4.4 cm) dial; 12" (30.5 cm) stem

0 18436 00210 9

THERMOCOUPLE THERMOMETERS



DTF572 – Rotating Display Thermocouple Thermometer

-40 to +572°F/-40 to +300°C

- 3-second response
- Field calibration
- Backlit extra-big digits
- 1.5 mm thin tip; 4.5" (11.5 cm) probe

0 18436 00493 6



TCT572-BK – Folding Thermocouple Thermometer - Black

-58 to +572°F/-50 to +300°C

- 3-second response
- Field calibration
- Backlit display
- Max/min
- 1.5 mm thin tip; 4.25" (10.8 cm) probe

0 18436 00465 3



TCTW572 – Waterproof Folding Thermocouple Thermometer

-58 to +572°F/-50 to +300°C

- 2-second response
- Waterproof (IPX7)
- One-button field calibration
- Backlit 4-way rotating display with extra-big digit
- 1.5 mm thin tip; 4.33" (11.0 cm) probe

0 18436 00508 7



INTP626X – Infrared/Thermocouple Probe Thermometer

Infrared: -67 to +482°F/-55 to +250°C;
Thermocouple: -67 to +626°F/-55 to +330°C

- Distance:spot = 2.5:1
- Laser target illumination
- HACCP check lights & icons
- Max, min, hold & lock
- 1.5 mm thin tip; 4.5" (11.43 cm) probe

0 18436 00576 6



INTP662 – Infrared Gun/Thermocouple Thermometer

Infrared: -76 to +662°F/-60 to +350°C;
Thermocouple: -76 to +662°F/-60 to +350°C

- Distance:Spot = 8:1
- Backlit HACCP check lights
- Max, min, hold & lock
- 8-beam laser target illumination
- 1.5 mm thin tip; 3.75" (9.53 cm) probe

0 18436 00572 8

INFRARED THERMOMETERS



IN482 – Infrared Thermometer, Timer & Clock

-67 to 482°F/-55 to +250°C; 24 hours by hr/
min/sec

- Distance:Spot = 5:1
- Max/min and lock
- Displays clock & room temp in standby

0 18436 00573 5



IN1022 – Infrared Gun

-76 to +1022°F/-60 to +550°C

- Distance:Spot = 12:1
- 8-beam laser target illumination
- Temperature alerts for HACCP compliance
- Max, min, difference, average & lock

0 18436 00571 1



INTP626X – Infrared/Thermocouple Probe Thermometer

Infrared: -67 to +482°F/-55 to +250°C;
Thermocouple: -67 to +626°F/-55 to +330°C

- Distance:spot = 2.5:1
- Laser target illumination
- HACCP check lights & icons
- Max, min, hold & lock
- 1.5 mm thin tip; 4.5" (11.43 cm) probe

0 18436 00576 6



INTP662 – Infrared Gun/Thermocouple Thermometer

Infrared: -76 to +662°F/-60 to +350°C;
Thermocouple: -76 to +662°F/-60 to +350°C

- Distance:Spot = 8:1
- Backlit HACCP check lights
- Max, min, hold & lock
- 8-beam laser target illumination
- 1.5 mm thin tip; 3.75" (9.53 cm) probe

0 18436 00572 8

DIGITAL PROBE THERMOMETERS



DTP392 – Probe Thermometer

32 to 392°F/0 to 200°C

- Monitors temperature while cooking
- Displays actual & set temps
- Audio/visual alert sounds when food is done
- 5.5" (14.0 cm) probe with 3' (91.4 cm) sensor cable

0 18436 00619 0



DTTC – Combo Probe Thermometer, Timer & Clock

14 to 392°F/-10 to +200°C; 24 hours by hr/min

- Monitors temperature while cooking or cooling
- Displays actual & set temps & timer or clock
- Timer counts up & down
- 5.5" (14.0 cm) probe with 3' (91.4 cm) sensor cable

White DTTC-W 0 18436 00620 6
 Silver DTTC-S 0 18436 00448 6



DTP482 – Programmable Probe Thermometer/Timer

14 to 482°F/0 to +250°C; 24 hours by hr/min

- Monitors temperature while cooking
- Preset & programmable
- Displays actual & set temps or timer
- 5.5" (14.0 cm) probe with 3' (91.4 cm) sensor cable

0 18436 00450 9



DTP572 – Dual Probe Thermometer

-58 to +572°F/-50 to +300°C

- Monitors temperatures while cooking
- Displays actual temperatures of both probes
- Audio/visual alert when food is done
- 2.5 mm reduced tip; 4" (11.2 cm) probes with 3' (91.4 cm) sensor cables

0 18436 00606 0



DSP1 – Dual-Sensing Probe Thermometer/Timer

32 to 572°F/0 to 300°C; 10 hrs by hr/min/sec

- Monitors food & oven temperatures while cooking
- Programmable
- Displays actual & set temps for both food & oven or timer
- Distinct alerts for food, oven & timer
- 6.75" (17.0 cm) probe with 39" (1 m) sensor cable

White DSP1-W 0 18436 00455 4
 Silver DSP1-S 0 18436 00444 8

CANDY & DEEP FRY THERMOMETERS



TCF400 – Candy & Deep Fry Thermometer

75 to 400°F/25 to 200°C

- Candy and deep fry stages
- Dishwasher safe
- Laboratory glass

0 18436 00501 8



TCG400 – Candy & Deep Fry Ruler Thermometer

100 to 400°F/40 to 200°C

- Candy & deep fry stages
- Dishwasher safe
- 8" (20.3 cm) color-coded scale

0 18436 00502 5



TCH130 – Chocolate Tempering Thermometer

40 to 130°F

- Dishwasher safe
- Laboratory glass
- Non-mercuric column

TCH130

0 18436 00504 9

TCH130C

Celsius

0 18436 00713 5



IRXL400 – Candy & Deep Fry Thermometer

100 to 400°F

- Candy stages
- Safe for commercial dishwashers
- Field calibration with tool on sheath
- 1.75" (4.4 cm) dial; 7" (17.8 cm) stem



IRXL400

0 18436 00204 8

IRXL400C

Celsius

0 18436 00725 9



IRL500 – Long Stem Fry Thermometer – 12"

100 to 500°F/38 to 260°C

- Safe for commercial dishwashers
- Boil test field calibration
- 1.75" (4.4 cm) dial; 12" (30.5 cm) stem

0 18436 00210 9



DTC450 – Digital Candy Thermometer

14 to 450°F/-10 to +232°C

- 7 preset candy stages with unique alerts
- 1 programmable all-purpose temperature stage
- 8.25" (21 cm) stem

0 18436 00506 3



DTW450L – Waterproof Thermometer – Long Stem

-40 to +450°F/-40 to +230°C

- 6-second response
- Safe for commercial dishwashers (IPX7)
- One-button field calibration
- 2.5 mm reduced tip; 8" (20.3 cm) stem

0 18436 00469 1



DTTC – Combo Probe Thermometer, Timer & Clock

14 to 392°F/-10 to +200°C; 24 hours by hr/min

- Monitors temperature while cooking or cooling
- Displays actual & set temps & timer or clock
- Timer counts up & down
- 5.5" (14.0 cm) probe with 3' (91.4 cm) sensor cable

White

DTTC-W

0 18436 00620 6

Silver

DTTC-S

0 18436 00448 6



BEVERAGE & FROTHING THERMOMETERS



IRT220-F – Beverage & Frothing Thermometer

0 to 220°F

- Frothing zone
- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1" (2.5 cm) magnified dial;
- 5" (12.7 cm) stem

0 18436 00221 5



IRB220-F – Beverage & Frothing Thermometer – 5" Stem

0 to 220°F/-18 to +104°C

- Frothing zone
- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1.5" (3.8 cm) magnified dial;
- 5" (12.7 cm) stem

IRB220-F

0 18436 00230 7

IRB220-F-C Celsius

0 18436 00733 3



IRB220-F-6.5 – Beverage & Frothing Thermometer – 6.5" Stem

0 to 220°F/-18 to +104°C

- Frothing zone
- Safe for commercial dishwashers
- Field calibration with tool on sheath
- 1.5" (3.8 cm) magnified dial;
- 6.5" (16.5 cm) stem

IRB220-F-6.5

0 18436 00235 2

IRB220-F-6.5-C Celsius

0 18436 00732 6



IRTL220 – Beverage & Frothing Thermometer – 7" Stem

0 to 220°F/-18 to +104°C

- Frothing zone
- Safe for commercial dishwashers
- Field calibration with tool on sheath
- 1.75" (4.4 cm) dial; 7" (17.8 cm) stem

0 18436 00220 8



SANITIZING AND WIPES



PW200 – Thermometer Probe Wipes - Packets

200 Single Use Packets

- FDA-listed, EPA & NQA certified
- 70% Isopropyl Alcohol
- Expiration date on package
- 1.2 x 2.2 in (3 x 5.5 cm) pads

0 18436 00906 1



PW1000 – Thermometer Probe Wipes - 5x200 Packets

5 Boxes of 200 Single Use Packets

- FDA-listed, EPA & NQA certified
- 70% Isopropyl Alcohol
- Expiration date on package
- 1.2 x 2.2 in (3 x 5.5 cm) pads

0 18436 00919 1

OVEN & GRILL THERMOMETERS



EOT1 – Oven Thermometer

100 to 600°F/50 to 300°C

- Temperature zones
- Ovenproof
- Laboratory glass lens

0 18436 00253 6



MOT1 – Multi-Mount Oven Thermometer

100 to 600°F/50 to 300°C

- Ovenproof
- Laboratory glass lens
- 3-way mounting: magnet, stand, hang

0 18436 00256 7



DOT2 – Oven Thermometer

150 to 550°F/70 to 280°C

- Temperature zones
- Ovenproof
- Laboratory glass lens

DOT2

0 18436 00251 2

DOT2C

Celsius

0 18436 00730 2





HOT1 – Hot Holding Thermometer

100 to 180°F/38 to 82°C

- Temperature zone
- Ovenproof
- Laboratory glass lens

0 18436 00258 1

NSF



POT750X – High Heat Oven Thermometer

100 to 750°F/50 to 400°C

- Ovenproof
- High heat
- Laboratory glass lens

0 18436 00240 6

NSF




GTS800X – Grill Surface Thermometer

100 to 800°F/40 to 425°C

- Temperature zones
- High heat
- Color-coded scale

0 18436 00486 8

NSF



REFRIGERATOR/FREEZER/AIR THERMOMETERS



NSF

EFG120 – Refrigerator/Freezer Thermometer

-40 to +120°F/-40 to +50°C

- Temperature zones
- Color-coded scale
- Non-mercuric column
- Private label options available

EFG120	Single	0 18436 00259 8
EFG120-X2	Twin Pack	0 18436 00265 9



NSF

FG80 – Refrigerator/Freezer Thermometer

-40 to +80°F/-40 to +27°C

- Temperature zones
- Shatterproof case
- Non-mercuric column

0 18436 00257 4



NSF

RFT1 – Refrigerator/Freezer Thermometer

-20 to +80°F/-30 to +30°C

- Temperature zones
- Laboratory glass lens
- 2-way mounting: stand, hang

RFT1		0 18436 00255 0
RFT1C	Celsius	0 18436 00711 1



TA20 – Audio/Visual Refrigerator/Freezer Alarm

-58 to +158°F/-50 to +70°C

- Audio/visual alert
- Signal sounds at 15 or 46°F (-9.5 or 8°C)
- Displays room & refrigerator/freezer temperatures
- 39" (1 m) sensor cable

0 18436 00520 9



AT120 – Air Thermometers

-40 to +120°F/-40 to +50°C

- Magnet or adhesive mounting
- 12 per box: 4 white, 4 black, 4 red
- 1.75" (4.4 cm) dial

AT120		0 18436 00100 3
AT120C	Celsius	0 18436 00714 2

DISHWASHER THERMOMETERS



DTW450 – Dishwasher Thin Tip Thermometer

-40 to +450°F/-40 to +230°C

- 6-second response
- Safe for commercial dishwashers (IPX7)
- One-button field calibration
- 1.5 mm thin tip; 4.5" (11.4 cm) stem

0 18436 00462 2



DW2 – Dishwasher Thermometer

32 to 194°F/0 to 90°C

- Simulates a plate surface to comply with FDA Food Code
- Waterproof (IP66)
- LED indication lights for different maximum temperatures
- Max/min; last maximum temperature recall
- Storage case included

0 18436 00498 1



TIMERS

Our broad collection of digital and mechanical timers feature quality construction and are designed for precise and consistent measurement of time. Responding to customers' needs, we've successfully developed a variety of custom products. If you do not see your ideal timer in our collection, please ask us about developing a new one for you.

DIGITAL HOUR/MINUTE TIMERS



TM2 – Digital Timer

20 hours by hr/min

- Counts down
- Stop & restart
- 3-way mounting: pocket clip, magnet, stand

TM2

0 18436 00350 2



TM4 – Loud Alarm Timer

20 hours by hr/min

- Counts down
- Big digit
- Loud alarm

0 18436 00408 0

DIGITAL HOUR/MINUTE/SECOND TIMERS



TM8 – Multi-Task Timer & Clock

24 hours by hr/min/sec

- Counts up & down
- Dual function
- Memory

0 18436 00403 5



TM30 – Direct Entry 2-Alarm Timer

10 hours by hr/min/sec

- Counts up & down
- Audio/vibrate alarm
- Loud & long alarm
- Last count recall

0 18436 00404 2



PT2 – 4-Event Timer & Clock

100 hours by hr/min/sec

- Counts up & down in 4 channels separately or simultaneously
- Individual channel sounds
- Programmable

0 18436 00400 4

DIGITAL MINUTE/SECOND TIMERS



TM28 – Mini Timer

100 minutes by min/sec

- Counts up & down
- Extra-big digit
- Last count recall

<input type="checkbox"/> White	TM28-W	0 18436 00421 9
<input type="checkbox"/> Silver	TM28-S	0 18436 00435 6
<input type="checkbox"/> Black	TM28-BK	0 18436 00414 1



TM7-W – Loud Alarm Timer

100 minutes by min/sec

- Counts down
- Big digit
- Last count recall

0 18436 00415 8



TM15 – Extra-Big Digit Timer

100 minutes by min/sec

- Counts up & down
- Extra-big digit
- Loud & long alarm
- Last count recall

0 18436 00441 7



TMW1 – Waterproof Timer

100 minutes by min/sec

- Counts up & down
- Heavy duty
- Extra-loud & long audio/visual alarm

0 18436 00301 4

MECHANICAL TIMERS



MTM3 – Mechanical Timer

1 hour by min

- Counts down
- Long 3-second alarm
- 2.625" (6.7 cm) diameter face

0 18436 00409 7



MT4 – Compact Mechanical Timer

1 hour by min

- Counts down
- Long 3-second alarm
- Stainless steel housing
- Non-slip rubber magnet

□ White	MT4-W	0 18436 00439 4
■ Black	MT4-BK	0 18436 00437 0
■ Silver	MT4-S	0 18436 00436 3
■ Red	MT4-R	0 18436 00413 4



MT1 – Heavy Duty Mechanical Timer

1 hour by min

- Counts down
- Long 3-second alarm
- Stainless steel housing

0 18436 00407 3



SCALES

Our collection of digital and mechanical scales feature quality construction and are designed for precise and consistent weight measurement. Responding to customers' needs, we've successfully developed a variety of custom products. If you do not see your ideal scale in our collection, please ask us about developing a new one for you.

MASTER SCALES



SD0204 – Digital High Precision Scale, 2 lb

2.2 LB/1000 G by lb:oz/kg.g

- Small profile
- Precise to 0.01 oz, 0.1 g
- Tare, hold & field calibration
- Platform: 5.35 W x 5.35 L in (13.6 W x 13.6 L cm), removable
- Resolution: 0.01 oz, 0.1 g

0 18436 00839 2



SD0502 – Digital Portion Control Scale, 5 lb

5 LB/2.27 KG by lb:oz/kg.g

- Small profile
- Tare, hold & field calibration
- Platform: 5.35 W x 5.35 L in (13.6 W x 13.6 L cm), removable
- Resolution: 0.1 oz, 1 g

0 18436 00818 7



SD1114 – Digital Portion Control Scale, 11 lb

11 LB/5 KG by lb:oz/kg.g

- Small profile
- Tare, hold & field calibration
- Platform: 5.35 W x 5.35 L in (13.6 W x 13.6 L cm), removable
- Resolution: 0.1 oz, 1 g

0 18436 00820 0



SD1112 – Digital Portion Control Scale, 11 lb

11 LB/5 KG by lb:oz/kg.g

- Medium profile
- Tare, hold & field calibration
- Platform: 7.12 W x 7.12 L (in)/ 18.1 W x 18.1 L (cm), removable
- Resolution: 0.1 oz, 1 g

0 18436 00817 0



SD2202 – Digital Portion Control Scale, 22 lb

22 LB/10 KG by lb:oz/kg.g

- Large profile
- Tare, hold & field calibration
- Platform: 11.40 W x 7.08 L in (29.0 W x 18.0 L cm), removable
- Resolution: 0.1 oz, 1 g

0 18436 00816 3



SD3302 – Digital Portion Control Scale, 33 lb

33 LB/15 KG by lb:oz/kg.g

- Large profile
- Tare, hold & field calibration
- Platform: 11.40 W x 7.08 L in (29.0 W x 18.0 L cm), removable
- Resolution: 0.2 oz, 5 g

0 18436 00815 6



SD5502 – Digital Portion Control Scale, 55 lb

55 LB/25 KG by lb:oz/kg.g

- Large profile
- Tare, hold & field calibration
- Platform: 11.40 W x 7.08 L in (29.0 W x 18.0 L cm), removable
- Resolution: 0.2 oz, 5 g

0 18436 00827 9

SUBMERSIBLE SCALES



SD1110X – Submersible Scale, 11 lb

11 LB/5 KG/176 OZ by lb:oz/lb:fr oz/lb/oz/fr oz/g

- Submersible (IP67)
- Programmable
- Tare & field calibration
- Platform: 7.2 W x 6.7 L in (18.2 W x 17.0 L cm), removable
- Resolution: 0 lb:0.1 oz, 0 lb:1/8 oz, 0.005 lb, 0.05 oz, 1/8 oz, 1 g

0 18436 00832 3



SD1120 – Submersible Scale, 11 lb

11 LB/5 KG/176 OZ by oz/fr oz/kg/g/lb:oz/
lb:fr oz/lb

- Low/high limit alerts with backlit display
- Submersible (IP68)
- Programmable
- Tare, hold & field calibration
- Platform: 5.38 x 5.38 in (13.7 x 13.7 cm), removable
- Resolution: 0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb

0 18436 00846 0



SD2210X – Submersible Scale, 22 lb

22 LB/10 KG/352 OZ by lb:oz/lb:fr oz/lb/oz/fr oz/g

- Submersible (IP67)
- Programmable
- Tare & field calibration
- Platform: 7.2 W x 6.7 L in (18.2 W x 17.0 L cm), removable
- Resolution: 0 lb:0.1 oz, 0 lb:1/8 oz, 0.005 lb, 0.05 oz, 1/8 oz, 1 g

0 18436 00833 0



SD2220 – Submersible Scale, 22 lb

22 LB/10 KG/352 OZ by oz/fr oz/kg/g/lb:oz/
lb:fr oz/lb

- Low/high limit alerts with backlit display
- Submersible (IP68)
- Programmable
- Tare, hold & field calibration
- Platform: 6.4 x 7 in (16.2 x 18.2 cm), removable
- Resolution: 0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb

0 18436 00847 7

ECONOMY SCALES



SD1104 – Digital Scale, 11 lb

11 LB/5 KG/176 OZ/5 L by lb:oz/fl oz/g/ml

- Tare
- Backlit display
- Stainless steel platform
- Platform: 5.5" (14 cm) diameter
- Resolution: 1 g, 0.1 fl oz, 0 lb:0.1 oz, 1 ml

■ Silver	SD1104-S	0 18436 00806 4
■ Black	SD1104-BK	0 18436 00807 1
■ Red	SD1104-R	0 18436 00808 8



SD2206 – Digital Portion Control Scale, 22 lb

22 LB/352 OZ/10 KG by lb:oz/oz/g

- Piece counting
- Backlit display
- Tare, hold & field calibration
- Removable stainless steel platform
- Platform: 5.9 W x 5.9 L in (15.0 W x 15.0 L cm), removable
- Resolution: 0 lb:0.1 oz, 0.1 oz, 2 g

0 18436 00834 7

GLASS SCALES



SD1502 – NSF® Digital Glass Scale, 15 lb

15 LB/7 KG by lb:oz/g

- Tare & hold
- Tempered glass
- Platform: 6.02 W x 9.17 L in (15.3 W x 23.3 L cm)
- Resolution: 0.1 oz, 1 g

■ Silver	SD1502-S	0 18436 00830 9
■ Black	SD1502-BK	0 18436 00831 6



PRECISION SCALES



SD0202 – Digital Precision Scale, 2.2 lb

2.2 LB/1000 G by oz/g

- Precise to 0.01 oz, 0.1 g
- Tare
- Removable stainless steel platform
- Platform: 4.45 W x 4.45 L in (11.3 W x 11.3 L cm)
- Resolution: 0.01 oz, 0.1 g

Gray	SD0202-GY	0 18436 00842 2
Red	SD0202-R	0 18436 00843 9
Green	SD0202-G	0 18436 00844 6
Blue	SD0202-B	0 18436 00845 3

SPECIALTY SCALES



SDC0602 – Coffee Scale & Timer, 6.5 lb

*3 KG/6.5 LB/3 L by g/oz/ml
& 100 minutes by min/sec*

- Precise to 0.1 g, 0.005 oz, 0.1 ml
- Tare
- Backlit digits
- Timer counts up
- Platform: 5.1 x 4.7 in (13 x 12 cm)
- Resolution: 0.1 g, 0.005 oz, 0.1 ml

0 18436 00828 6

RECEIVING SCALES



SDR220 – Digital Shipping & Receiving Scale, 220 lb

220 LB/100 KG by lb:oz/kg

- Programmable preset unit
- Tare & field calibration
- Extendable display
- Platform: 11 W x 12 L in (28 W x 30.6 L cm)
- Resolution: 2 oz, 50 g

0 18436 00828 6



CALIBRATION WEIGHTS



WT100 – Calibration Weight, 100 g

- For calibrating kitchen scales
- Tapered top for easy handling
- OIML Class: M2

0 18436 00829 3



WT500 – Calibration Weight, 500 g

- For calibrating kitchen scales
- Tapered top for easy handling
- OIML Class: M2

0 18436 00825 5



WT02 – Calibration Weight, 2 kg

- For calibrating kitchen scales
- Tapered top for easy handling
- OIML Class: M2

0 18436 00824 8




WT05 – Calibration Weight, 5 kg

- For calibrating kitchen scales
- Tapered top for easy handling
- OIML Class: M2

0 18436 00823 1



MERCHANDISING & DISPLAYS



D-TRI5 – Triangle Dolly

- Three 2' x 5' grids on casters
- Includes grids, dolly, joiner clips & hooks
- FREE with qualifying purchase

0 18436 00980 1



IRT220-PACK – Cooking Thermometer Display Pack

0 to 220°F

- Safe for commercial dishwashers
- Field calibration with wrench on sheath
- 1" (2.5 cm) magnified dial; 5" (12.7 cm) stem
- 12 per pack

IRT220-PACK

0 18436 00205 5

IRT220C-PACK Celsius

0 18436 00211 6



AT120 – Air Thermometers

-40 to +120°F/-40 to +50°C

- Magnet or adhesive mounting
- 12 per box: 4 white, 4 black, 4 red
- 1.75" (4.4 cm) dial








AT120

0 18436 00100 3

AT120C Celsius

0 18436 00714 2

ACCESSORIES

Model	Description	UPC
AD-LR44	1.5 V Button Battery – Available in packs of six only	0 18436 00900 9
AD-F 	Stainless Steel Clip – For 5"/12.7 cm stem thermometers	0 18436 00910 8
AD-L	Stainless Steel Clip – For 7"/17.8 cm stem thermometers	0 18436 00920 7
AD-N 	Stainless Steel Clip – For 6.5"/16.5 cm stem thermometers	0 18436 00970 2
AD-Z 	Stainless Steel Clip – For 7"/17.8 cm stem thermometers	0 18436 00917 7
AD-P	Stainless Steel Clip – For digital probe thermometers	0 18436 00930 6
AD-DTP392	Replacement Probe – For DTP392 thermometers	0 18436 00950 4
AD-DTTC	Replacement Probe – For DTTC thermometers	0 18436 00940 5
AD-DTP482	Replacement Probe – For DTP482 thermometers	0 18436 00960 3
AD-DSP1	Replacement Probe – For DSP1 thermometers	0 18436 00903 0
AD-AC3302	AC Adapter – For SD0204, SD0502, SD1114, SD1112, SD2202, SD3302, SD5502 & SDR220 scales	0 18436 00921 4
AD-AC1110X	AC Adapter – For SD1110X, SD1120, SD2210X & SD2220 scales	0 18436 00929 0
AD-PF0502 	Stainless Steel Platform – For SD0502 & SD1114 scales	0 18436 00926 9
AD-PF1112 	Stainless Steel Platform – For SD1112 scales	0 18436 00925 2
AD-PF3302 	Stainless Steel Platform – For SD2202, SD3302 & SD5502 scales	0 18436 00923 8
AD-PF1110X 	Stainless Steel Platform – For SD1110X & SD2210X scales	0 18436 00931 3

A GLOBAL CATEGORY LEADER

CDN is a global category leader in measurement tools, known for quality and innovation.

Our measurement tools range from the basic to the unique. When you stock our thermometers, timers and scales, you bring quality and value to your customers — from the novice cook to the accomplished chef.

CDN was named “Best Overall Company” in its category by the prestigious Stevie Awards for Women in Business. We are also a certified member of the Women’s Business Enterprise National Council (WBENC).

CDN Technology

Pro
Accurate

Quick-Read



CDN Affiliations



CDN Certifications



For more detailed information on our products, please visit **CDNmeasurement.com** or call **800-338-5594**.



All products have a five year limited warranty unless otherwise noted. 5-Year Limited Warranty: Any instrument that proves to be defective in material or workmanship (excluding batteries) within five years of original purchase will be repaired or replaced without charge upon receipt of the unit prepaid at: CDN, PO Box 10947, Portland, OR 97296-0947. This warranty does not cover damage in shipment or failure caused by failure to adhere to the accompanying instructions, inadequate maintenance, normal wear and tear, tampering, accident, misuse, unauthorized modification, obvious carelessness or abuse. CDN shall not be liable for any consequential or incidental damages whatsoever.

PO Box 10947 Portland, OR 97296-0947
800 338-5594 | info@CDNmeasurement.com
CDNmeasurement.com