

## Digital Folding Thermometer

**Models: DT572-BK (Black), DT572-R (Red), DT572-G (Green), DT572-B (Blue)**

Compact folding thermistor with fast 4-second response, 1.7 mm thin tip, IPX6 waterproof rating and hold mode. Available in the HACCP colors of Black (roasts), Red (meat), Green (produce) and Blue (seafood).



Features	Big digit, hold, on/off button, auto-off, selectable units
Measurement Range	-58 to +572°F/-50°C to +300°C
Unit of Measure	°F (°C)
Accuracy	32 to 212°F (0 to 100°C): ±2°F (1°C); -4 to 30°F (-20 to -1°C) & 214 to 302°F (101 to 150°C): ±4°F (2°C); -58°F to -6°F (-50 to -21°C) & 304 to 392°F (151 to 200°C): ±8°F (4°C); 394 to 572°F (201 to 300°C): ±5%
Heat Resilience	High heat
Water Resilience	IPX6: protected from powerful water jets (12.5mm nozzle) from any direction
Response Time	4-second response
On/Off	On/off button
Auto-off	Auto-off after 10 minutes
Housing Material	Food-safe ABS
Display Material	LCD
Display Size	1.14 W x 0.51 H in (2.9 W x 1.3 H cm)
Digit Height	10 mm
Probe Type	Thermistor
Probe Material	304 stainless steel
Probe Length	3.375" (8.6 cm) stem
Probe Diameter	1.7 mm thin tip
Resolution	0.1°F (0.1°C)
Mounting	Magnet, loop
Temperature Guide	USDA safe food temperature guide in instructions
Operating Range	32 to 104°F (0 to 40°C), ≤90% RH
Storage Range	14 to 140°F (-10 to 60°C)
Battery	One 3V CR2032 button battery (WERCSmart) included
Battery Life	12 months
Dimensions	1.57 W x 5.08 L x 0.67 D in (4.0 W x 12.9 L x 1.7 D cm)
Weight	1.8 oz (52 g) (including battery)
UPC	DT572-BK: 0 18436 00509 4, DT572-R: 0 18436 00515 5, DT572-G: 0 18436 00516 2, DTL572-B: 0 18436 00517 9
Certification	NSF <sup>®</sup> Certified, WEEE, CE
Warranty	5-Year Limited Warranty