

Digital Portion Control Scale, 5 lb

Model: SD0502

This exclusive NSF[®] Certified scale was designed for demanding foodservice kitchens. It features tare, hold and field calibration to ensure accuracy over time. Small profile and BioCote[®] antimicrobial technology. Batteries and AC adapter included.



Features	Small profile, tare, hold, field calibration, removable stainless steel platform, selectable units, overload indication, battery status indication, on/off button, auto-off, AC adapter
Measurement Range	5 lb/2.27 kg capacity
Unit of Measure	lb:oz/kg.g
Resolution	0.1 oz, 1 g
Accuracy	1 kg ±3g; 2 kg ±6g
Tare	Tare
Calibration	Field calibration
Water Resilience	IP54: protected from water splashes from any direction for 10 minutes; dust protected
Response Time	0.125 second response
On/Off	On/off button
Auto-off	Auto-off after 2 minutes; disabled when the AC adapter is used
Housing Material	Food-safe ABS
Display Material	LCD
Display Size	3.35 W x 0.866 H in (8.5 W x 2.2 H cm)
Load Cell	Single point load cell
Platform Material	304 stainless steel
Platform Size	5.35 W x 5.35 L in (13.6 W x 13.6 L cm)
Operating Range	32 to 104°F (0 to 40°C), ≤90% RH
Power	AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (500mA) output
Battery	Two AAA alkaline batteries (WERCSmart) included
Battery Life	2 years (3 times/day, 30 s/time)
Dimensions	5.90 W x 1.75 H x 7.87 D in (15.0 W x 4.45 H x 20.0 D cm)
Weight	18.5 oz (524 g) (including battery)
UPC	0 18436 00818 7
Certification	NSF [®] Certified, WEEE, CE
Antimicrobial Protection	BioCote [®]
Warranty	1-Year Limited Warranty
Optional Accessories	2 kg calibration weight (WT02), 500 g calibration weight (WT500), Small Profile Platform (AD-PF0502), AC Adapter (AD-AC3302) not NSF [®] Certified
Replacement Parts	Small Profile Platform (AD-PF0502), AC Adapter (AD-AC3302) not NSF [®] Certified