

Submersible Scales

Submersible Scale, 11 lb

Model: SD1120

This NSF® Certified, heavy-duty stainless steel scale was designed for demanding foodservice kitchens. It is sturdy and waterproof, featuring low/high limit alerts with color-coded backlit display. Programmable and field calibration feature to ensure accuracy over time. Power adapter included.



Measurement Range 11 lb/5 kg/176 oz capacity Unit of Measure oz, f oz, kg, g, lb.oz, lb/ oz, lb Resolution 0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb Accuracy 2 kg ± 6; 5 kg ± 15 g Tare Tare Calibration Field calibration Water Resilience lP68: protected from water up to 4.9 feet/1.5 meters for up to 60 minutes, completely protected against dust Alert/Alarm Low/high limit alerts with backlit display On/Off On/off button Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material 304 stainless steel, food-safe ABS Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 32 to 104°F (15 to 40°C), 3e5% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Batte	Features	Low/high limit alerts with backlit display, programmable, tare, hold, field calibration, removable stainless steel platform, selectable units, stability indication, overload indication, low battery & charging indication, on/off button, auto-off, AC adapter
Resolution 0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb Accuracy 2 kg ±6 g; 5 kg ±15 g Tare Tare Calibration Field calibration Water Resilience IP68: protected from water up to 4.9 feet/1.5 meters for up to 60 minutes, completely protected against dust Alert/Alarm Low/high limit alerts with backlit display On/Off On/off button Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material LCD Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (16 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), 685% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) ou	Measurement Range	11 lb/5 kg/176 oz capacity
Accuracy 2 kg ±6 g; 5 kg ±15 g Tare Tare Calibration Field calibration Water Resilience IF68: protected from water up to 4.9 feet/1.5 meters for up to 60 minutes, completely protected against dust Alert/Alarm Low/high limit alerts with backlit display On/Off On/off button Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material LCD Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (16 to 40°C), 385% RH Storage Range 32 to 104°F (0 to 40°C), 385% RH Storage Range 32 to 104°F (0 to 40°C), 485% RH Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) <th< td=""><td>Unit of Measure</td><td>oz, / oz, kg, g, lb:oz, lb:/ oz, lb</td></th<>	Unit of Measure	oz, / oz, kg, g, lb:oz, lb:/ oz, lb
Tare Tare Calibration Field calibration Water Resilience P68: protected from water up to 4.9 feet/1.5 meters for up to 60 minutes, completely protected against dust Alert/Alarm Low/high limit alerts with backlit display On/Off On/Off On/off button Auto-off Auto-off Ater 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material 304 stainless steel, food-safe ABS Display Material LCD Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), \$45% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Resolution	0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb
Calibration Field calibration Water Resilience IP68: protected from water up to 4.9 feet/1.5 meters for up to 60 minutes, completely protected against dust Alert/Alarm Low/high limit alerts with backlit display On/Off On/off button Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material 304 stainless steel, food-safe ABS Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 9) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Accuracy	2 kg ±6 g; 5 kg ±15 g
Water Resilience IP68: protected from water up to 4.9 feet/1.5 meters for up to 60 minutes, completely protected against dust Alert/Alarm Low/high limit alerts with backlit display On/Off On/off button Auto-off atter 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material LCD Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Tare	Tare
Alert/Alarm Low/high limit alerts with backlit display On/Off On/off button Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material 304 stainless steel, food-safe ABS Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), 30-85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery Life 10 months Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limit	Calibration	Field calibration
On/Off On/Off button Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material 304 stainless steel, food-safe ABS Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), <85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Water Resilience	
Auto-off Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used Housing Material 304 stainless steel, food-safe ABS Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Alert/Alarm	Low/high limit alerts with backlit display
Housing Material 304 stainless steel, food-safe ABS Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	On/Off	On/off button
Display Material LCD Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Auto-off	Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used
Display Size 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) Digit Height 20 mm Backlight Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range Load Cell Single point load cell Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104° F (15 to 40° C), 30° 85% RH Storage Range 32 to 104° F (0 to 40° C), 40° F (85% RH Power AC Adapter: 100° 240 VAC 100° F (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Housing Material	304 stainless steel, food-safe ABS
Digit Height20 mmBacklightThree-color backlit display for low/high limit alerts: red = high, blue = low, green = in rangeLoad CellSingle point load cellPlatform Material304 stainless steelPlatform Size5.38 W x 5.38 L in (13.7 W x 13.7 L cm)Operating Range59 to 104°F (15 to 40°C), 30-85% RHStorage Range32 to 104°F (0 to 40°C), ≤85% RHPowerAC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) outputBattery4.8V 1800mAh built-in rechargeable battery (WERCSmart)Battery Life10 monthsDimensions5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm)Weight28.4 oz (805 g) (including battery)UPC0 18436 00846 0CertificationNSF® Certified, WEEE, CEWarranty1-Year Limited WarrantyOptional Accessories5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Display Material	LCD
BacklightThree-color backlit display for low/high limit alerts: red = high, blue = low, green = in rangeLoad CellSingle point load cellPlatform Material304 stainless steelPlatform Size5.38 W x 5.38 L in (13.7 W x 13.7 L cm)Operating Range59 to 104°F (15 to 40°C), 30-85% RHStorage Range32 to 104°F (0 to 40°C), ≤85% RHPowerAC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) outputBattery4.8V 1800mAh built-in rechargeable battery (WERCSmart)Battery Life10 monthsDimensions5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm)Weight28.4 oz (805 g) (including battery)UPC0 18436 00846 0CertificationNSF® Certified, WEEE, CEWarranty1-Year Limited WarrantyOptional Accessories5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Display Size	2.6 W x 1.06 H in (6.6 W x 2.7 H cm)
Load CellSingle point load cellPlatform Material304 stainless steelPlatform Size5.38 W x 5.38 L in (13.7 W x 13.7 L cm)Operating Range59 to 104°F (15 to 40°C), 30-85% RHStorage Range32 to 104°F (0 to 40°C), ≤85% RHPowerAC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) outputBattery4.8V 1800mAh built-in rechargeable battery (WERCSmart)Battery Life10 monthsDimensions5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm)Weight28.4 oz (805 g) (including battery)UPC0 18436 00846 0CertificationNSF® Certified, WEEE, CEWarranty1-Year Limited WarrantyOptional Accessories5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Digit Height	20 mm
Platform Material 304 stainless steel Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Backlight	Three-color backlit display for low/high limit alerts: red = high, blue = low, green = in range
Platform Size 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Load Cell	Single point load cell
Operating Range 59 to 104°F (15 to 40°C), 30-85% RH Storage Range 32 to 104°F (0 to 40°C), ≤85% RH Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Platform Material	304 stainless steel
Storage Range32 to 104°F (0 to 40°C), ≤85% RHPowerAC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) outputBattery4.8V 1800mAh built-in rechargeable battery (WERCSmart)Battery Life10 monthsDimensions5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm)Weight28.4 oz (805 g) (including battery)UPC0 18436 00846 0CertificationNSF® Certified, WEEE, CEWarranty1-Year Limited WarrantyOptional Accessories5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Platform Size	5.38 W x 5.38 L in (13.7 W x 13.7 L cm)
Power AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output Battery 4.8V 1800mAh built-in rechargeable battery (WERCSmart) Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Operating Range	59 to 104°F (15 to 40°C), 30-85% RH
Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Storage Range	32 to 104°F (0 to 40°C), ≤85% RH
Battery Life 10 months Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Power	AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (1000mAh) output
Dimensions 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Battery	4.8V 1800mAh built-in rechargeable battery (WERCSmart)
Weight 28.4 oz (805 g) (including battery) UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Battery Life	10 months
UPC 0 18436 00846 0 Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Dimensions	5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm)
Certification NSF® Certified, WEEE, CE Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Weight	28.4 oz (805 g) (including battery)
Warranty 1-Year Limited Warranty Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	UPC	0 18436 00846 0
Optional Accessories 5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified	Certification	NSF® Certified, WEEE, CE
	Warranty	1-Year Limited Warranty
Replacement Parts AC Adapter (AD-AC1110X) not NSF® Certified	Optional Accessories	5 kg Calibration Weight (WT05), AC Adapter (AD-AC1110X) not NSF® Certified
	Replacement Parts	AC Adapter (AD-AC1110X) not NSF® Certified



Tel 800 338-5594 **Fax** 800 879-2364 **Web** CDNmeasurement.com

© 11-2024 CDN CD2921100 - 11/24